

total coat Finish

Ready to use!

High gloss top coat for
Total Coat Coatings.

Industrial, agricultural and automotive use
World class waterborne technology

www.chemicar.com • www.totalcoat.mx

total coat Finish

Product Identifier:
TCF
Total Coat Finish



WARNING

Harmful if swallowed.
Causes skin irritation.
Causes eye irritation.

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. IF SWALLOWED: Call a Poison Center or doctor/physician if you feel unwell. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws, regulations and product characteristics at time of disposal.

Supplier Identification:
Chemicar USA 670 New York St. Memphis TN 38104
Tel: 901-274-3347 Fax: 901-274-8816
See SDS for further information.



Industrial Equipment



Underbody



Pick Up Beds

Directions for use:

Total Coat Finish is a glossy top coat to be applied over Total Coat HD or Total Coat Undercoating to change the appearance from matte black to glossy. TC Finish cannot be used by itself as an undercoating or abrasion protection coating and can only be applied on top of Total Coat products.

Apply at minimum 55 F with Relative Humidity of min 40%. Apply only on top of TC products that are properly dried. Clean up with w~~at~~ rags and water while coating is still wet. Dried Finish can only be removed mechanically. When applying Finish on an old coating i.e. to refresh a worn bed liner, properly clean the old coating before spraying. A high pressure washer is highly recommended.

Make sure all oil, grease, solvents and wax are removed by using a citrus-based cleaner. Rinse with plenty of clean water. Surface to be coated must be dry.

Use a properly filtered and de-humidified air supply at 30 – 45 psi.

Mask off where necessary and remove masking tape before Finish dries.

Attach the Chemicar Economy gun (model RA/88) directly to the bottle.

Apply a coat 0.5 mm thick. Drying requires a min temp of 55 F. Additional heat and/or ventilation will speed up the drying process.

Forced drying under direct heavy sun is not recommended.

Any repair can be done over the existing coating after drying.

Small sections can be repaired with a paint brush.

1 bottle covers 20 sq ft.

Wash the spray gun thoroughly with clean water immediately after use.

TC Finish is ready to use, do not add water or solvent. Avoid continuous water contact or heavy use during the first week after application.

THIS PRODUCT HAS BEEN LABELED ACCORDING TO GHS DIRECTIVES.

Contents: 1 US Quart

Made in Mexico

Keep from freezing

